Pasta cookers



General characteristics

- Surface tops manufactured in 1.5 mm thick AISI-304 stainless steel.
- Laser-cut joints, automatic welding and polished.
- 1.5 mm thick AISI-316L stainless steel wells built into the surface top.
- 2 well sizes
- · GN-2/3 wells, with 26 litre capacity
- · GN-1/1 wells, with 40 litre capacity
- The well is filled through the inlet solenoid valve with a two-position switch: average and high-speed filling.
- Well drainage through a mechanical ball valve which is resistant to high temperatures and has a safety overflow.

- Automatic safety system to stop the current if the water runs out.
- Controls with a protective support base and system to prevent water infiltration.
- Machines with IPX5 grade water protection. GAS MODELS
- High-performance stainless-steel burner located outside of the well with a combustion chamber that enables heating of the base and sides of the well (up to the minimum filling level)
- Burner ignition through electronic spark igniter. With an access tube for manual ignition
- Heating controlled through safety valve.

ELECTRIC MODELS

- AISI 304 stainless-steel heating elements located inside the well to directly heat the water.
- Heating controlled through energy regulator.
- Voltage: 400 V 3+N. For other voltages, consult the options at the end of the chapter.
 Standard provision
- 26 L models: 2 x 1/3 baskets per well
- 40 L models: 3 x 1/3 baskets per well

Optional accessories: (See accessories page at the end of the chapter)

- 6 x 1/6 square baskets kit
- 6 x 1/6 round baskets kit
- 4 x ¼ baskets kit
- 2 x ½ baskets kit

MODEL	GAS	CODE	WELL			TOTAL POWER (kW)	DIMENSIONS (mm)	€
			QUANTITY	SIZE	BASKETS (1/3)	- (٨٧٧)		
🎳 Gas pasta cod	okers							
CP-G7126	LPG	19071621	1	NG-2/3	2	10,00	400x730x850	-
	NG	19074728						
CP-G7226	LPG	19071360	2	NG-2/3	4	20,00	800x730x850	-
	NG	19074729						
CP-G7140	LPG	19098553	1	NG-1/1	3	16,50	400x730x850	-
	NG	19098554						
CP-G7240	LPG	19098555	2	NG-1/1	6	33,00	800x730x850	-
	NG	19098556						
Electric pasta	cookers							
CP-E7126	-	19071569	1	NG-2/3	2	9,00	400x730x850	-
CP-E7226	-	19072437	2	NG-2/3	4	18,00	800x730x850	-
CP-E7140	-	19074747	1	NG-1/1	3	12,00	400x730x850	-
CP-E7240	-	19074780	2	NG-1/1	6	24,00	800x730x850	-