



**Catalogue**  
**FOOD SERVICE**  
**Chapter**  
**DISHWASHING**

**Specific model**  
**WGP-401 S B 230V1N50Hz**

19110498

01/04/2025

**DENOMINATION:**

Glasswasher concept plus range for 400x400 basket with rinse pump, smart softener and drain pump.

**DESCRIPTION :**

**INTERFACE**

- 2.8" backlit colour (TFT) liquid crystal display.
- Colour-coded status indicators.
- Display of operating parameters, such as tank and boiler temperature or cycle time.
- Indicators of tank and boiler heater operation.
- Self-diagnosis and error signalling.
- Timer function to be able to schedule the machine to switch on or off at a specific time.
- Power-saving mode (stand-by): Reduction of power consumption when the machine is not in operation.
- User-selectable programmes according to equipment use (glass, crockery and bar) and machine-specific programmes.
- Technical menu (via password):
  - View of all the inputs of the electronics and act on the outputs to facilitate the quick detection of problems.
  - Modification of operating parameters, such as heating temperatures, washing and rinsing times, etc.
- Membrane keypad with 5 buttons.

**PROGRAMMES:**


- Programmes for glass - as standard:
  - Light: 90s (2,1 l/cycle, Wash T<sup>a</sup>: 60°C, Rinse T<sup>a</sup>: 65°C)
  - Standard: 120s (2,1 l/cycle, Wash T<sup>a</sup>: 60°C, Rinse T<sup>a</sup>: 65°C)
  - Intensive: 180s (2,1 l/cycle, Wash T<sup>a</sup>: 60°C, Rinse T<sup>a</sup>: 65°C)
  - Cold rinse: 90s (2,1 l/cycle, Wash T<sup>a</sup>: 65°C, Rinse T<sup>a</sup>: 65°C)
- Additional programmes:
  - Programmes for crockery
  - Programmes for bar

**CONSTRUCTION DETAILS**

- Sides of the washing chamber in partial double-skin.
- Stamped tank with slope for a complete drainage.
- Stamped basket guides.
- Upper and lower wash and rinse arms.
- Door:
  - Soundproofed and heat-resistant double-skin door.
  - Magnetic micro switch to stop the cycle in case of accidental opening of the door.
- Double in stages filtering system:
  - Polypropylene pump suction filter that blocks the lightest dirt, protecting the washing pump. It has a blue indicator on the overflow or filter depending on the model, to indicate that it is part of the "colour identification" concept.
  - Composite tank surface filters as standard, retain coarse dirt. The filter can be easily removed without disassembling the wash and rinse arms.
  - Dual-flow wash pumps: one input and two outputs, one for each arm, without the need to split the flow to avoid power loss and reduce noise.
  - Soft-start: The cycle starts slowly and gradually increases to maximum speed to prevent light items such as glassware and crockery from falling out.
- Wash/rinse arms. Duo-KLIP:
  - A combined wash and rinse arm at the same level, made of composite

**DIMENSIONS**

X Width	466 mm	X Gross width	530 mm
Y Depth	535 mm	Y Gross depth	680 mm
Z Height	725 mm	Z Gross height	890 mm
Net Weight	38,0 kg	Gross Weight	43,0 kg
Net volume	0,181 m <sup>3</sup>	Gross volume	0,321 m <sup>3</sup>



**ELECTRICITY TECHNICAL SPECIFICATIONS**

Electric power	3,490 kW
Voltage	220-240V
Phases	1N
Electric frequency	50Hz
Amperage (A)	15,17
Engine power	0,29 kW
Heating power	3,20 kW

**WATER TECHNICAL SPECIFICATIONS**

Pressure	H2O: 100-400kPa (1-4bar)
Maximum Temperature	Water Inlet Max Temp: 60°C

**CONNECTIONS TECHNICAL SPECIFICATIONS**

Single-phase 230V wiring	3G 1,5MM <sup>2</sup> - 16A
Drain 1 diameter	17MM

**OTHERS**

IPX	IPX3
-----	------

**TECHNICAL FEATURES**

Height glasses	285
Diameter plates	300
Max.theor.product.(baskets/h)	40
Tank capacity	9 L
Tank heater power	0,80 kW
Washing pump power	0,29 kW
Drain pump power	0,04 kW
Boiler capacity	4 L
Rinsing pump power	0,130 kW
Boiler heater power	2,40 kW
Type of heating (Alt./Sim.)	Simultaneous





**Catalogue**  
**FOOD SERVICE**  
**Chapter**  
**DISHWASHING**

**Specific model**  
**WGP-401 S B 230V1N50Hz**

19110498

01/04/2025

material, preventing the two arms from getting in each other's way.

- Low friction and very light arm that allows all the power supplied by the pump to be used for washing dishes and not for rotating the arm.
- Washing and rinsing orifices designed with specific geometry to reach the most inaccessible places. They spray water precisely, achieving 10% lower water consumption, reducing electricity and chemical consumption and therefore helping to minimize operating costs.
- The clip-on snap-on coupling makes it easy to assemble and disassemble for cleaning.
- Rinse pump:
  - Rinse even at low mains pressure (1 bar). Water is drawn from the boiler through a booster pump and sent to the rinse nozzles of the machine ensuring optimum and constant pressure. This system, being independent of mains pressure, thanks to the presence of the "Air Break", leads to lower water consumption and therefore lower energy consumption.
  - The temperature of the water in the boiler is constant throughout the rinse, as this water has not been mixed with cold mains water during the refilling phase.
  - The "Air Break" system prevents backflow into the water supply system of non-potable water contaminated with rinse products, detergents and food waste. Type A nonreturn device in compliance with EN 1717.
  - Accurate rinse aid dosing with a constant water flow.
  - Thermostop: Starts the rinse when the rinse temperature required for a hygienic wash result and correct drying of the dishes has been reached. The rinse cycle will be extended to a maximum time of ten minutes if the rinse temperature setpoint is not reached.
  - Thermostatic filling: Speeds up the machine set-up time as the tank is filled with water previously heated in the boiler, which is more powerful. Only available for models with rinse pump.
  - Smart softener (S):
    - For best washing results and to protect the machine, with an integrated softener. It saves space and provides continuous soft water. This allows the detergent and rinse aid to work to their full effect and considerably reduces limescale deposits in the machine.
    - The user can easily refill the tank and a sensor warns when the salt tank needs to be refilled.
  - Smart resin regeneration:
    - \* Integrated softener that provides continuous soft water. This allows the detergent and rinse aid to work to their full effect and considerably reduces limescale deposits in the machine.
    - \* It performs the regeneration fully automatically and invisibly for the customer.
    - \* Water quality is always constant.
  - Sensorisation (Z) including:
    - Chemical dosing control (DA).
    - Control of low chemical level by means of probes (L), available as an accessory, with warning on the control panel.
    - Peristaltic rinse aid dosing as standard.
  - Drain pump included (B).
  - Volumetric rinse: the dirty wash water is partially drained before rinsing, which makes it possible:
    - Avoid useless waste of detergent by slower soiling of the water.
    - Reducing energy costs during the heating phase of the wash water by continuously regenerating the wash

**POSSIBLE OPTIONS :**

- Detergent dispenser
- Connectivity





**Catalogue**  
FOOD SERVICE  
**Chapter**  
DISHWASHING

**Specific model**  
WGP-401 S B 230V1N50Hz

19110498

01/04/2025

- Round basket
- Double skin
- Glass rod basket

**STANDARD OPTIONS :**

- Drain pump
- Sensorisation

**POSSIBLE ACCESSORIES :**

- BASKETS FOR DISHWASHERS
- BASKETS FOR GLASSES
- ACCESSORIES DISHWASHING
- STANDS
- VARIOUS KITS

**SUPPLIED ACCESSORIES:**

- 19082432 Glass basket, 400x400x110 mm. 2
- 19084452 Insert for 11 plates, 400x400x110 mm. 1
- 19102721 Cutlery basket for 9 pieces of cutlery, 96 mm diameter and 104 mm 1 height.






**Catalogue**  
FOOD SERVICE  
**Chapter**  
DISHWASHING

**Specific model**  
WGP-401 S B 230V1N50Hz

19110498

01/04/2025



A: ENTRADA DE AGUA G3/4"  
B1: DESAGÜE Ø25 L=2000 mm  
B2: DESAGÜE CON BOMBA Ø17 L=1875mm  
C: ALIMENTACIÓN ELÉCTRICA  
D: ETHERNET  
E: DOBLE PARED L=10mm

A: WATER INLET G3/4"  
B1: DRAIN Ø25 L=2000 mm  
B2: DRAINAGE PUMP Ø17 L=1875mm  
C: ELECTRICAL CONNECTION  
D: ETHERNET  
E: DOUBLE SKIN L=10mm

A: ARRIVÉE D'EAU G3/4"  
B1: VIDANGE Ø25 L=2000 mm  
B2: POMPE À VIDANGE Ø17 L= 1875mm  
C: CONNEXION ÉLECTRIQUE  
D: ETHERNET  
E: DOUBLE MUR L=10mm