



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CUN-11S 230V 1N 50Hz

19089505

17/07/2024

The photo may show the standard model and not the configured one

DENOMINATION:

Snack freezing upright, single body with 1 door.

DESCRIPTION :

- Interior and exterior built-in with food grade stainless steel for intensive professional applications.
- 50 mm thickness, CFC-free, high-density (40 kg/m³) polyurethane insulation, injected under high pressure.
- Constructed with a rail system placed in the front and back of the upright with 18 grid level position and 70mm distance among them.
- Intuitive, digital display for electronic control with energy saving function to ensure an optimal control of storing products.
- Removable pull-out/push-in magnetic door gasket to keep maximum hygiene and maintain the insulating properties
- Hinged doors with automatic return for a perfect closing that minimize temperature gain. Doors have a 120° dwell position and close automatically at less than 90°
- Automatic evaporation of defrost water.
- Internally designed forced draft cooling system with low consumption electronic components to guarantee optimal equipment efficiency and performance.
- Optimal air circulation system that guarantees a balanced and constant distribution throughout the equipment, so that the temperature remains uniform. It helps preserve food for longer.
- Height-adjustable stainless steel legs. Height of the legs can be adjusted individually (130 mm - 200 mm) to enable convenient cleaning.
- Low energy consumption LED lighting horizontally located in the interior of compartment.
- Stamped edge interiors, for easier cleaning operations to reduce potential dirt traps with a built-in drainage to get rid of waste liquid inside units.
- Removable and height adjustable epoxy coated 560x542 size grids with a maximum loading capacity of up to 40 kg.
- Stainless steel doors with ergonomic, full-length, robust, perfectly integrated handle. that ensures practical opening and avoids dust and dirt collection.
- Defrost by a heating element to remove ice accumulated in the evaporator.
- Equipped with 3x 560x542 grid per each full door.

POSSIBLE OPTIONS :

- 60 Hz
- Stainless Backing
- Wheels Kit (Factory Assembly)
- Locks
- Opposite Opening
- Remote group


STANDARD OPTIONS :

- Door frame resistance

POSSIBLE ACCESSORIES :

- ACCESSORIES FOR REFRIGERATION

DIMENSIONS



X Width	693 mm	X Gross width	780 mm
Y Depth	726 mm	Y Gross depth	800 mm
Z Height	2067 mm	Z Gross height	2084 mm
Net Weight	114,0 kg	Gross Weight	120,0 kg
Net volume	1,040 m ³	Gross volume	1,300 m ³

ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	0,350 kW
Voltage	230V
Phases	1N
Electric frequency	50Hz
Amperage (A)	2,6 A

COLD TECHNICAL SPECIFICATIONS

Temperature	-18 -22 °C
Climate class	4
Refrigeration power	0,364 kW
GWP	3
Cooling gas load	90,000 g
Gross internal volume	506 L
Noise level	58,00 dB
Condensation system	Vent.
Model Type	Vertical cabinet
Annual elec. consumption	2777,65 kWh
Power consumption 24h	7,61 kWh
Frozen net.vol	386 L
IEE	82
Clasif. Energy efficiency	E

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1+T-4A
--------------------------	----------

OTHERS

Number of doors	1
-----------------	---





Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CUN-11S 230V 1N 50Hz

19089505

17/07/2024

The photo may show the standard model and not the configured one

SUPPLIED ACCESSORIES:

- 19097772 Epoxi grid for snack upright. 3



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CUN-11S 230V 1N 50Hz

19089505

17/07/2024

