



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CUN-24S 230V 1N 50Hz

19089513

17/07/2024

The photo may show the standard model and not the configured one

DENOMINATION:

Snack freezing upright, double body with 4 doors.

DESCRIPTION :

- Interior and exterior built-in with food grade stainless steel for intensive professional applications.
- 50 mm thickness, CFC-free, high-density (40 kg/m³) polyurethane insulation, injected under high pressure.
- Constructed with a rail system placed in the front and back of the upright with 18 grid level position and 70mm distance among them.
- Intuitive, digital display for electronic control with energy saving function to ensure an optimal control of storing products.
- Removable pull-out/push-in magnetic door gasket to keep maximum hygiene and maintain the insulating properties
- Hinged doors with automatic return for a perfect closing that minimize temperature gain. Doors have a 120° dwell position and close automatically at less than 90°
- Automatic evaporation of defrost water.
- Internally designed forced draft cooling system with low consumption electronic components to guarantee optimal equipment efficiency and performance.
- Optimal air circulation system that guarantees a balanced and constant distribution throughout the equipment, so that the temperature remains uniform. It helps preserve food for longer.
- Height-adjustable stainless steel legs. Height of the legs can be adjusted individually (130 mm - 200 mm) to enable convenient cleaning.
- Low energy consumption LED lighting horizontally located in the interior of compartment.
- Stamped edge interiors, for easier cleaning operations to reduce potential dirt traps with a built-in drainage to get rid of waste liquid inside units.
- Removable and height adjustable epoxy coated 560x542 size grids with a maximum loading capacity of up to 40 kg.
- Stainless steel doors with ergonomic, full-length, robust, perfectly integrated handle. that ensures practical opening and avoids dust and dirt collection.
- Defrost by a heating element to remove ice accumulated in the evaporator.
- Equipped with 3x 560x542 grid per each full door and 3x 500x154 grid in the middle beam for increasing loading capacity.

POSSIBLE OPTIONS :

- 60 Hz
- Stainless Backing
- Wheels Kit (Factory Assembly)
- Remote group

STANDARD OPTIONS :


- Door frame resistance

POSSIBLE ACCESSORIES :

- ACCESSORIES FOR REFRIGERATION

SUPPLIED ACCESSORIES:

DIMENSIONS



X Width	1388 mm	X Gross width	1470 mm
Y Depth	726 mm	Y Gross depth	800 mm
Z Height	2067 mm	Z Gross height	2084 mm
Net Weight	214,0 kg	Gross Weight	227,0 kg
Net volume	2,083 m ³	Gross volume	2,451 m ³

ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	0,613 kW
Voltage	230V
Phases	1N
Electric frequency	50Hz
Amperage (A)	3,5 A

COLD TECHNICAL SPECIFICATIONS

Temperature	-18 -22 °C
Climate class	4
Refrigeration power	0,735 kW
GWP	3
Cooling gas load	138,000 g
Gross internal volume	1109 L
Noise level	58,00 dB
Condensation system	Vent.
Model Type	Vertical cabinet
Annual elec. consumption	4855,00 kWh
Power consumption 24h	13,30 kWh
Frozen net.vol	868 L
IEE	84
Clasif. Energy efficiency	E

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1,5+T-6A
--------------------------	------------

OTHERS

Number of doors	4
-----------------	---





Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CUN-24S 230V 1N 50Hz

19089513

17/07/2024

The photo may show the standard model and not the configured one

- 19097772 Epoxi grid for snack upright. 6
- 19097785 Epoxi grid for double body snack upright. 3



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CUN-24S 230V 1N 50Hz

19089513

17/07/2024

