



**Catalogue**  
FOOD SERVICE  
**Chapter**  
REFRIGERATION

**Specific model**  
CUD-22S/M FH 230V 1N 50Hz

19089515

17/07/2024

The photo may show the standard model and not the configured one

**DENOMINATION:**

Snack dual temperature upright, double body with 2 doors.

**DESCRIPTION :**

- Interior and exterior built-in with food grade stainless steel for intensive professional applications.
- 50 mm thickness, CFC-free, high-density (40 kg/m<sup>3</sup>) polyurethane insulation, injected under high pressure.
- Constructed with a rail system placed in the front and back of the upright with 18 grid level position and 70mm distance among them.
- Intuitive, digital display for electronic control with energy saving function to ensure an optimal control of storing products.
- Removable pull-out/push-in magnetic door gasket to keep maximum hygiene and maintain the insulating properties
- Hinged doors with automatic return for a perfect closing that minimize temperature gain. Doors have a 120° dwell position and close automatically at less than 90°
- Automatic evaporation of defrost water.
- Internally designed forced draft cooling system with low consumption electronic components to guarantee optimal equipment efficiency and performance.
- Optimal air circulation system that guarantees a balanced and constant distribution throughout the equipment, so that the temperature remains uniform. It helps preserve food for longer.
- Height-adjustable stainless steel legs. Height of the legs can be adjusted individually (130 mm - 200 mm) to enable convenient cleaning.
- Low energy consumption LED lighting horizontally located in the interior of compartment.
- Stamped edge interiors, for easier cleaning operations to reduce potential dirt traps with a built-in drainage to get rid of waste liquid inside units.
- Removable and height adjustable epoxy coated 560x542 size grids with a maximum loading capacity of up to 40 kg.
- Stainless steel doors with ergonomic, full-length, robust, perfectly integrated handle. that ensures practical opening and avoids dust and dirt collection.
- Equipped with 3 560x542 grid per each full door with a maximum loading capacity of up to 40 kg.

**POSSIBLE OPTIONS :**

- 60 Hz
- Stainless Backing
- Wheels Kit (Factory Assembly)
- Door frame resistance
- Locks

**POSSIBLE ACCESSORIES :**


- ACCESSORIES FOR REFRIGERATION

**SUPPLIED ACCESSORIES:**

- 19014778 Tray support guides for GN 2/1 double body upright. 3
- 19097772 Epoxi grid for snack upright. 6

**DIMENSIONS**

X Width	1388 mm	X Gross width	1470 mm
Y Depth	726 mm	Y Gross depth	800 mm
Z Height	2067 mm	Z Gross height	2084 mm
Net Weight	227,0 kg	Gross Weight	240,0 kg
Net volume	2,083 m <sup>3</sup>	Gross volume	2,451 m <sup>3</sup>



**ELECTRICITY TECHNICAL SPECIFICATIONS**

Electric power	0,533 kW
Voltage	230V
Phases	1N
Electric frequency	50Hz
Amperage (A)	0,81 A

**GAS TECHNICAL SPECIFICATIONS**

Gas type 2	R-290
------------	-------

**COLD TECHNICAL SPECIFICATIONS**

Cooling gas load 2	90,000 g
Refrigeration power 2	0,364 kW
Temperature 2	-22 -18 °C
Temperature	0 +8 °C
Climate class	4
Refrigeration power	0,361 kW
GWP	3
Cooling gas load	92,000 g
Gross internal volume	1012 L
Noise level	62,00 dB
Condensation system	Vent.

**CONNECTIONS TECHNICAL SPECIFICATIONS**

Single-phase 230V wiring	2X1,5+T-2A
--------------------------	------------

**OTHERS**

Number of doors	2
-----------------	---





**Catalogue**  
FOOD SERVICE  
**Chapter**  
REFRIGERATION

**Specific model**  
CUD-22S/M FH 230V 1N 50Hz

19089515

17/07/2024

