



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CCP-2B 230V 1N 50Hz

19102582

19/07/2024

The photo may show the standard model and not the configured one

DENOMINATION:

Pastry 800 depth refrigerated counter with 2 doors and forced air refrigeration equipment with evaporator.

DESCRIPTION :


- Interior constructed with AISI-304 stainless steel exterior in food grade stainless steel.
- 50 mm thickness, CFC-free, high-density (40 kg/m³) polyurethane insulation, injected under high pressure.
- Heavy-duty stainless-steel working top with 100mm high splash-back, preventing spillage behind the counter.
- Intuitive, digital display for electronic control with energy saving function to ensure an optimal control of storing products.
- Stainless steel doors with ergonomic, full-length, robust, perfectly integrated handle that avoids dust and dirt collection.
- Removable pull-out/push-in magnetic door gasket to keep maximum hygiene and maintain the insulating properties.
- Hinged doors with automatic return for a perfect closing that minimize temperature gain. Doors have a 120° dwell position and close automatically at less than 90°.
- Pivotal front panel with easy access for service access and ventilation grid design allowing machine to be embedded without penalizing performance.
- Internally designed forced draft cooling system with low consumption electronic components to guarantee optimal equipment efficiency and performance.
- Optimal air circulation system that guarantees a balanced and constant distribution throughout the equipment, so that the temperature remains uniform. It helps preserve food for longer.
- Height-adjustable stainless steel legs. Height of the legs can be adjusted individually (130 mm - 200 mm) to enable convenient cleaning.
- Automatic evaporation of defrost water.
- Stamped edge interiors, easier cleaning operations to reduce potential dirt traps with a built-in drainage to get rid of waste liquid inside units.
- Removable and height adjustable epoxy coated EN60x40 grids with a maximum loading capacity of up to 40 kg.
- Equipment with 1 EN60x40 grids and height adjustable 2 sets of tray slides per each full door.
- Defrost by compressor stop.

POSSIBLE OPTIONS :

- Stainless Backing
- Wheels Kit (Factory Assembly)
- Door frame resistance
- Granite countertop
- Locks
- Left group
- Without breastplate
- Without Countertop
- Panoramic aperture
- Remote group

POSSIBLE ACCESSORIES :

DIMENSIONS



X Width	1492 mm	X Gross width	1605 mm
Y Depth	800 mm	Y Gross depth	880 mm
Z Height	850 mm	Z Gross height	1000 mm
Net Weight	115,0 kg	Gross Weight	121,0 kg
Net volume	1,015 m ³	Gross volume	1,412 m ³

ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	0,262 kW
Voltage	230V
Phases	1N
Electric frequency	50Hz
Amperage (A)	1,1A

COLD TECHNICAL SPECIFICATIONS

Temperature	0 +8 °C
Climate class	4
Refrigeration power	0,369 kW
GWP	3
Cooling gas load	110,000 g
Noise level	54,00 dB
Condensation system	Vent.
Model Type	Counter Cabinet
Annual elec. consumption	1477,00 kWh
Power consumption 24h	4,05 kWh
Refrigeration net.vol	279 L
IEE	59
Clasif. Energy efficiency	D

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1+T-2A
--------------------------	----------

OTHERS

Number of doors	2
-----------------	---





Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CCP-2B 230V 1N 50Hz

19102582

19/07/2024

The photo may show the standard model and not the configured one

- REFRIGERATION
- ACCESSORIES FOR REFRIGERATION

SUPPLIED ACCESSORIES:

- 19033557 Tray support guides for pastry counters, L=649 mm. 4
- 19097776 EN60x40 epoxy grid for pastry upright. 2



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CCP-2B 230V 1N 50Hz

19102582

19/07/2024

