



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
RPS-2GZ 230V 1N 50Hz

19105615

05/07/2024

The photo may show the standard model and not the configured one

DENOMINATION:

Pizza worktop saladette with 2 doors.

DESCRIPTION :

- Specially manufactured in high-quality stainless steel for intensive professional applications, featuring a very robust design and perfect finishing.
- Stainless steel drawers with perforated bottom plates and telescopic sliding guides, capable of complete retraction, to economize working surface. Other drawer configurations are also available upon request.
- Static evaporator, foamed in CFC free high-density polyurethane with 40 mm thickness. Interior without fin evaporator and smooth surfaces make an easy to clean compartment.
- Stainless steel doors with ergonomic, full-length, robust, perfectly integrated handle that avoids dust and dirt collection.
- Intuitive, digital display for electronic control with energy saving function to ensure an optimal control of storing products.
- Automatic evaporation of defrost water.
- Removable pull-out/push-in magnetic door gasket to keep maximum hygiene and maintain the insulating properties.
- Forced air cooling system.
- Removable front panel with front breathing design allowing machine to be embedded without penalizing performance.
- Removable and height adjustable epoxy coated GN 1/1 grids with a maximum loading capacity of up to 40 kg.
- 30 mm CFC free polyurethane injected stainless Steel worktop with open area for GN1/6 containers.

POSSIBLE OPTIONS :

- Drawers [1/2] unit
- Remote group

STANDARD OPTIONS :

- Panoramic aperture


POSSIBLE ACCESSORIES :

- ACCESSORIES FOR REFRIGERATION

SUPPLIED ACCESSORIES:

- 19014778 Tray support guides for GN 2/1 double body upright. 2
- 19104363 GN 1/1 epoxy grid for saladette counters. 2

DIMENSIONS



X Width	894 mm	X Gross width	940 mm
Y Depth	700 mm	Y Gross depth	760 mm
Z Height	955 mm	Z Gross height	1120 mm
Net Weight	56,0 kg	Gross Weight	64,0 kg
Net volume	0,598 m3	Gross volume	0,800 m3

ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	0,245 kW
Voltage	230V
Phases	1N
Electric frequency	50Hz
Amperage (A)	1,4A

COLD HORECA ECO LABEL

Temperature	+2 +8 °C
Climate class	4
Refrigeration power	0,369 kW
Gas type	R-290
GWP	3
Cooling gas load	80,000 g
Noise level	55,60 dB
Condensation system	Vent.

CONNECTIONS TECHNICAL SPECIFICATIONS

230 V three-phase wiring	3X1,0MM2
--------------------------	----------

OTHERS

Number of doors	2
-----------------	---




Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
RPS-2GZ 230V 1N 50Hz

19105615

05/07/2024



Model	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	
RPS-2GP	894	840	822	20	21	861	
RPS-2G NS							
RPS-2G NS HH						-	850
RPS-2G NS DH					30		
RPS-2GS						290	1140
RPS-2GZ					105	955	
RPS-3GP	1358	840	822	20	21	861	
RPS-3G NS							
RPS-3G NS HHH						-	850
RPS-3G NS DHH							
RPS-3G NS DDH					30		
RPS-3GS			850	832		290	1140
RPS-3GZ						105	955
RPS-3G GR							
RPS-3G GR D6						160	1010