



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
UP-251

19089735

08/07/2024

The photo may show the standard model and not the configured one

DENOMINATION:

Professional refrigerated cabinet with 2 shelves.

DESCRIPTION :

- Exterior finishing: White coated galvanized steel.
- Removable pull-out/push-in magnetic door gasket to keep maximum hygiene and maintain the insulating properties
- Hinged doors with automatic return for a perfect closing that minimize temperature gain. Doors have a 120° dwell position and close automatically at less than 90°.
- CFC-free, high-density (40 kg/m³) polyurethane insulation, injected under high pressure.
- Rounded edge interiors, for easier cleaning operations to reduce potential dirt traps with a built-in drainage to get rid of waste liquid inside units.
- Intuitive, digital display for electronic control with energy saving function to ensure an optimal control of storing products.
- ON/OFF power switch.
- Door designed for easy opening orientation modification.
- Interior constructed with white coated galvanized steel.
- Doors with ergonomic, full-length, robust, perfectly integrated handle. that ensures practical opening and avoids dust and dirt collection.
- Internally designed forced draft cooling system with the evaporator integrated in the back side of the upright guarantees optimal cold distribution, efficiency and performance.
- Optimal air circulation system that guarantees a balanced and constant distribution throughout the equipment, so that the temperature remains uniform. It helps preserve food for longer.

POSSIBLE OPTIONS :

- 60 Hz


POSSIBLE ACCESSORIES :

- ACCESSORIES FOR REFRIGERATION

SUPPLIED ACCESSORIES:

- 19106512 Epoxi grid for UP-250. 2
- 19106517 Steel grid support. 2

DIMENSIONS



X Width	626 mm	X Gross width	715 mm
Y Depth	600 mm	Y Gross depth	647 mm
Z Height	850 mm	Z Gross height	975 mm
Net Weight	47,0 kg	Gross Weight	50,0 kg
Net volume	0,319 m ³	Gross volume	0,451 m ³

ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	0,091 kW
Voltage	230V
Phases	1N
Electric frequency	50Hz
Amperage (A)	0,72A

COLD HORECA ECO LABEL

CLIMATE_CLASS_OPERATION	STANDARD
Energy Efficiency Index	23,56 %
Typo C.1	CHILLED_OPERATING_TEMPERATU
Temperature	0 +8 °C
Climate class	4
Refrigeration power	0,140 kW
Gas type	R-600a
GWP	3
Cooling gas load	29,000 g
Gross internal volume	125 L
Noise level	43,00 dB
Condensation system	Static
Model Type	Counter Cabinet
Annual elec. consumption	487,64 kWh
Power consumption 24h	1,34 kWh
Refrigeration net.vol	112 L
IEE	24
Clasif. Energy efficiency	A

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1,5+T - 6 A
--------------------------	---------------





Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
UP-251

19089735

08/07/2024

