



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
UP-651

19089737

08/07/2024

The photo may show the standard model and not the configured one

DENOMINATION:

Professional refrigerated cabinet with 3 (GN+2/1)+1 shelves.

DESCRIPTION :

- Exterior finishing: White coated galvanized steel.
- Removable pull-out/push-in magnetic door gasket to keep maximum hygiene and maintain the insulating properties
- Hinged doors with automatic return for a perfect closing that minimize temperature gain. Doors have a 120° dwell position and close automatically at less than 90°.
- CFC-free, high-density (40 kg/m³) polyurethane insulation, injected under high pressure.
- Rounded edge interiors, for easier cleaning operations to reduce potential dirt traps with a built-in drainage to get rid of waste liquid inside units.
- Intuitive, digital display for electronic control with energy saving function to ensure an optimal control of storing products.
- ON/OFF power switch.
- Door designed for easy opening orientation modification.
- Interior constructed with white coated galvanized steel.
- Doors with ergonomic, full-length, robust, perfectly integrated handle that ensures practical opening and avoids dust and dirt collection.
- Internally designed static cooling system. Interior shelves built-in epoxy coated copper pipes, acts as an evaporator to cool down the products.
- Ice defrosting process needs to be done manually.
- 400 and 600 models with 7 levels of grills and 235mm distance among them.
- 200 models with 3 levels and 200mm distance among them.

POSSIBLE OPTIONS :

- 60 Hz
- Wheels Kit (Factory Assembly)


POSSIBLE ACCESSORIES :

- ACCESSORIES FOR REFRIGERATION

SUPPLIED ACCESSORIES:

- 19106515 Epoxi grid for UP-650. 3
- 19106516 Epoxi grid for UP-650. 1

DIMENSIONS



X Width	780 mm	X Gross width	820 mm
Y Depth	740 mm	Y Gross depth	780 mm
Z Height	1865 mm	Z Gross height	2010 mm
Net Weight	80,0 kg	Gross Weight	93,0 kg
Net volume	1,076 m ³	Gross volume	1,286 m ³

ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	0,186 kW
Voltage	230V
Phases	1N
Electric frequency	50Hz
Amperage (A)	1.3A

COLD HORECA ECO LABEL

CLIMATE_CLASS_OPERATION	STANDARD
Energy Efficiency Index	65,76 %
Tipo C.1	CHILLED_OPERATING_TEMPERATU
Temperature	0 +8 °C
Climate class	4
Refrigeration power	0,292 kW
Gas type	R-600a
GWP	3
Cooling gas load	82,000 g
Gross internal volume	600 L
Noise level	43,00 dB
Condensation system	Static
Model Type	Vertical cabinet
Annual elec. consumption	954,00 kWh
Power consumption 24h	2,61 kWh
Refrigeration net.vol	511 L
IEE	66
Clasif. Energy efficiency	D

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1,5+T - 6 A
--------------------------	---------------

