



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
UP-451 GD

19089742

08/07/2024

The photo may show the standard model and not the configured one

DENOMINATION:

Professional display refrigerated cabinet with 3+1 shelves.

DESCRIPTION :

- Exterior finishing: White coated galvanized steel.
- Removable pull-out/push-in magnetic door gasket to keep maximum hygiene and maintain the insulating properties
- Hinged doors with automatic return for a perfect closing that minimize temperature gain. Doors have a 120° dwell position and close automatically at less than 90°.
- CFC-free, high-density (40 kg/m³) polyurethane insulation, injected under high pressure.
- Rounded edge interiors, for easier cleaning operations to reduce potential dirt traps with a built-in drainage to get rid of waste liquid inside units.
- Intuitive, digital display for electronic control with energy saving function to ensure an optimal control of storing products.
- ON/OFF power switch.
- Door designed for easy opening orientation modification.
- Interior constructed with white coated galvanized steel.
- Double-glazed doors insulated with low thermal emissivity to reduce heat transfer with ergonomic handle.
- Internally designed forced draft cooling system with the evaporator integrated in the back side of the upright guarantees optimal cold distribution, efficiency and performance.
- Optimal air circulation system that guarantees a balanced and constant distribution throughout the equipment, so that the temperature remains uniform. It helps preserve food for longer.
- Low energy consumption LED lighting horizontally located in the frame.
- 400 and 600 model equipped with 4 removable and height adjustable epoxy coated grids.
- 200 model equipped with 2 removable and height adjustable epoxy coated grids.

POSSIBLE OPTIONS :

- 60 Hz
- Wheels Kit (Factory Assembly)

STANDARD OPTIONS :

- Glass door


POSSIBLE ACCESSORIES :

- ACCESSORIES FOR REFRIGERATION

SUPPLIED ACCESSORIES:

- 19106513 Epoxi grid for UP-450. 3
- 19106514 Epoxi grid for UP-450. 1

DIMENSIONS



X Width	626 mm	X Gross width	666 mm
Y Depth	740 mm	Y Gross depth	780 mm
Z Height	1865 mm	Z Gross height	2010 mm
Net Weight	82,0 kg	Gross Weight	93,0 kg
Net volume	0,864 m ³	Gross volume	1,044 m ³

ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	0,193 kW
Voltage	230V
Phases	1N
Electric frequency	50Hz
Amperage (A)	1.3A

COLD HORECA ECO LABEL

Energy Efficiency Index	18,99 %
Temperature	+2 +8 °C
Climate class	3
Refrigeration power	0,292 kW
Gas type	R-600a
GWP	3
Cooling gas load	82,000 g
Gross internal volume	459 L
Noise level	43,00 dB
Condensation system	Static
Model Type	1 refrigeration comp equipment
Annual elec. consumption	1023,82 kWh
Power consumption 24h	2,81 kWh
Energy efficiency Index (EEI)	18,9
Clasif. Energy efficiency	B

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1,5+T - 6 A
--------------------------	---------------

