



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
UP-651 SS GD

19100116

08/07/2024

The photo may show the standard model and not the configured one

DENOMINATION:

Professional display refrigerated cabinet (stainless steel exterior) with 7 shelves and glass door.

DESCRIPTION :

- Exterior made of stainless steel.
- Inner body made of ABS food grade material.
- Rounded edges and corners on the inside for easy cleaning.
- Door with built-in handle.
- Reversible door.
- Fitted with key lock as standard.
- Digital thermometer with temperature control.
- Working voltage: 230 V - 50 Hz.
- Interior constructed with white coated galvanized steel.
- Double-glazed doors insulated with low thermal emissivity to reduce heat transfer with ergonomic handle.
- Internally designed forced draft cooling system with the evaporator integrated in the back side of the upright guarantees optimal cold distribution, efficiency and performance.
- Optimal air circulation system that guarantees a balanced and constant distribution throughout the equipment, so that the temperature remains uniform. It helps preserve food for longer.
- Low energy consumption LED lighting horizontally located in the frame.
- 400 and 600 model equipped with 4 removable and height adjustable epoxy coated grids.
- 200 model equipped with 2 removable and height adjustable epoxy coated grids.

POSSIBLE OPTIONS :

- Wheels Kit (Factory Assembly)
- Opposite Opening

STANDARD OPTIONS :

- Glass door


POSSIBLE ACCESSORIES :

- ACCESSORIES FOR REFRIGERATION

SUPPLIED ACCESSORIES:

- 19106515 Epoxi grid for UP-650. 3
- 19106516 Epoxi grid for UP-650. 1

DIMENSIONS



X Width	780 mm	X Gross width	820 mm
Y Depth	740 mm	Y Gross depth	780 mm
Z Height	1865 mm	Z Gross height	2010 mm
Net Weight	91,0 kg	Gross Weight	104,0 kg
Net volume	1,076 m3	Gross volume	1,286 m3

ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	0,193 kW
Voltage	230V
Phases	1N
Electric frequency	50Hz
Amperage (A)	1.32A

COLD HORECA ECO LABEL

Energy Efficiency Index	14,99 %
Temperature	+2 +8 °C
Climate class	3
Refrigeration power	0,292 kW
Gas type	R-600a
GWP	3
Cooling gas load	82,000 g
Gross internal volume	600 L
Noise level	43,00 dB
Condensation system	Static
Model Type	1 refrigeration comp equipment
Annual elec. consumption	1095,00 kWh
Power consumption 24h	3,00 kWh
Energy efficiency Index (EEI)	14,9
Clasif. Energy efficiency	B

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1,5+T - 6 A
--------------------------	---------------

