



Cooking

Electric solid tops



General characteristics

- Surface tops manufactured in 2 mm thick AISI-304 stainless steel, designed to prevent liquids spilt from the pans from penetrating into the cooker.
- Laser-cut joints, automatic welding and polished.
- "Solid-top" models with four heating elements beneath the 15 mm thick cast steel fry-top, distributed so as to heat the four quadrants of the fry-top independently.
- Power control for each heating element. This allows the user to work with different temperature gradients on the fry-top.- Interior fan to lower the temperature of the components.
- Stamped surface with rounded corners for easy cleaning.
- High temperature enamelled cast iron flue protector.
- Access to the components from the front.



- Machines with IPX5 grade water protection.

OVEN

- Easy to use static GN 2/1 size oven with the controls positioned on the upper panel for better ergonomics.
- Stainless steel cooking chamber, making it easier to clean and providing better hygiene.
- Tray introduced sideways for easier handling.
- Guides at three heights to offer different working options.
- Guides with "U" shape to prevent the trays from tipping.

- Thermostatic temperature control (125 – 310 °C).
- Heating by means of stainless steel shielded heating elements with selector switch to operate the upper and/or lower zone.
- Oven floor manufactured in 6 mm cast iron, guaranteeing better performance and even heat distribution.
- Fibreglass closing seal to improve the oven's thermal efficiency.
- Dismountable oven door to facilitate repair.

VOLTAGE: 400 V 3+N . Ask for other voltages.

	MODEL	CODE	FRY-TOP		OVEN			TOTAL POWER (kW)	DIMENSIONS (mm)	€
			MEASUREMENTS	COOKING AREAS	POWER (kW)	SIZE	POWER (kW)			
Solid Top										
	C-E910	19075495	720x720	4	4x4	-	-	16,00	800x930x290	-
With oven										
	C-E911	19075498	720x720	4	4x4	GN-2/1	6,00	22,00	800x930x850	-