## Gas cookers



## General characteristics

- Stamped surface tops manufactured in 1.5 mm thick AISI-304 stainless steel
- Laser-cut joints and automatic welding. Hidden screws
- 397 x 580 mm double grates (397 x 290 mm for each burner) enabling the use of large pots and pans. The reduced distance of 75 mm between the central bars makes it possible to use pots with a very small diameter (8 cm), avoiding the risk of smaller pans tipping over.
- The grates are made of RAAF enamelled cast iron (resistant to alkaline and acid products, fire and high temperatures).
- Double-crown burners and diffusers made of nickel-plated cast iron which guarantee an even distribution of heat from the flame to the base of the pans, even for large pans. This therefore prevents heat from building up in a specific point and optimises energy transfer to the product.
- Burners of different strengths to adapt to containers and for use with different foods:
- · 5.25 kW (Ø 100 mm),
- · 8.0 kW(Ø 120 mm),
- Burners are easy to position
- Low-consumption pilot light and thermocouple located within the body of the burner for greater protection.
- Flexible stainless-steel gas pipes, facilitating internal manipulations in order to make repairs easier.

- Controls with a protective support base and system to prevent water infiltration.
- High-temperature enamelled cast iron flue protector which is flush with the grates therefore improving manoeuvrability, supporting larger containers and increasing the usable surface area.
- Access to components from the front.

## OVEN

- Possibility of choosing between a static gas oven with dimensions NG 2/1 or a side-opening English-style oven with dimensions 860 x 570 x 410 mm with a side-opening double door or an electric oven with dimensions NG 2/1.
- Cooking chamber made entirely of stainless steel, which makes cleaning easier and ensures greater hygiene.
- Trays are inserted sideways which improves manoeuvrability.
- Heating:
- · Gas: Tubular stainless-steel burner with pilot light and thermocouple and piezoelectric ignition.
- · Electric: Heating through stainless steel heating elements with selector switch for operation of the upper and/or inner part.
- Thermostatic valve for temperature control (125 310  $^{\circ}$ C).

- Rails on three height levels to offer different cooking options.
- Rails with anti-tipping system to prevent trays from overturning.
- Cast iron oven floor which guarantees better performance and uniform heat distribution.
- Fibreglass closing seal to improve the thermal efficiency of the oven and ensure its durability.
- Stamped oven frame and inner door, ensuring a better oven closure.
- Detachable oven door to facilitate repairs.

Optional accessories (See accessories page at the end of the chapter)

- Frying plate to place on 5.25 kW burners.
- Water column.
- Brass transmitters.

MODEL	GAS	CODE	GRILLS (mm)	BURNERS		OVEN		TOTAL POWER (kW)	DIMENSIONS	€
				5,25 KW	8 KW	SIZE	POWER (kW)			
Тор										
C-G720 -	LPG	19068008	397x290	2	-	-	-	10,50	400x730x290	-
	NG	19074175								
C-G720 H -	LPG	19068057	397x290	-	2	-	-	16,00	400x730x290	-
	NG	19074760								
C-G740 -	LPG	19060614	397x290	3	1	-	-	23,75	800x730x290	-
	NG	19073557								
C-G740 H -	LPG	19068058	397x290	-	4	-	-	32,00	800x730x290	-
	NG	19074761								
C-G760 -	LPG	19068059	397x290	4	2	-	-	37,00	1200x730x290	-
	NG	19074762								
C-G760 H -	LPG	19068110	397x290	-	6	-	-	48,00	1200x730x290	-
	NG	19074763								
Gas static over	en NG 2/1									
C-G741 -	LPG	19058530	397x290	3	1	NG-2/1	8,60	32,35	800x730x850	_
	NG	19073558								
C-G741 H -	LPG	19068112	397x290	-	4	NG-2/1	8,60	40,60	800x730x850	_
	NG	19074765								
C-G761 -	LPG	19071404	397x290	4	2	NG-2/1	8,60	45,60	1200x730x850	-
	NG	19073560								
C-G761 H -	LPG	19071463	397x290	-	6	NG-2/1	8,60	56,60	1200x730x850	-
	NG	19074766								
British style g										
C-GB761 -	LPG	19074812	397x290	4	2	860X570X410	8,60	45,60	1200x730x850	-
	NG	19074813								
C-GB761 R -	LPG	19074814	397x290	4	2	860X570X410	8,60	45,60	1200x730x850	-
	NG	19074815								
C-GB761 H -	LPG	19074816	397x290	-	6	860X570X410	8,60	56,60	1200x730x850	-
	NG	19074817								
C-GB761RH -	LPG	19074819	397x290	-	6	860X570X410	8,60	56,60	1200x730x850	-
Electric static	NG NG NG	19074820								
C-GE741 -		19074821	397x290	3	1	NG-2/1	6,00	29,75	800x730x850	-
	LPG									
C-GE741 H =	NG	19074822	397x290	-	4		6,00	38,00	800x730x850	-
	LPG	19074823				NG-2/1				
	NG	19074824								

H MODELS: With high-power burners R MODELS: With wheels