



Catalogue
FOOD SERVICE
Chapter
COOKING

Specific model
FT-G905 V L NG 230V 1N

19101458

30/05/2023

DENOMINATION:

GN gas frytop with security valve with thermocouple, smooth hot-plate, half module, 900 range.


DESCRIPTION :

- Surface tops manufactured in 2 mm thick AISI-304 stainless steel.
- Laser-cut joints, automatic welding and polishes. Screws hidden from view.
- Fry-tops manufactured in 20 mm thick mild steel, high powered and with rapid temperature attainment.
- Rapid reaction and recovery times of the fry-top temperature.
- The fry-tops are integrated into the funnelled surface top.
- The funnelled housing with rounded edges and corners make them very easy to clean.
- Fry-top tilted towards the front to facilitate fat and liquid collection.
- Fitted with an opening for the collection of cooking fat and storage tray with a capacity of up to 2 litres depending on the model.
- Option of easily dismountable side and back splash guards.
- High temperature enamelled cast iron flue protector.
- Access to the components from the front.
- Machines with IPX5 grade water protection.
- Smooth hot-plate.
- "- Gas heated model with burners with two branches.
- Operation by security valve with thermocouple.
- Ignition by electronic spark train. Have access tube for manual ignition.
- "

POSSIBLE ACCESSORIES :

- STANDS 900
- ACCESSORIES KORE
- FRY-TOP ACCESSORIES KORE
- TALL CHIMNEY KORE

DIMENSIONS



| | | | |
|------------|----------|----------------|----------|
| X Width | 400 mm | X Gross width | 440 mm |
| Y Depth | 930 mm | Y Gross depth | 1022 mm |
| Z Height | 290 mm | Z Gross height | 535 mm |
| Net Weight | 70,0 kg | Gross Weight | 88,0 kg |
| Net volume | 0,110 m3 | Gross volume | 0,241 m3 |

ELECTRICITY TECHNICAL SPECIFICATIONS

| | |
|--------------------|-----------|
| Electric power | 0,100 kW |
| Amperage (A) | 2A |
| Voltage | 230V - 1N |
| Electric frequency | 50/60Hz |

GAS TECHNICAL SPECIFICATIONS

| | |
|-----------------|--------------------------------|
| Gas type | NG |
| Gas power | 9,25 kW |
| Gas consumption | 0,978 m3/h |
| Regulated | NG G20/G25/G25.1 20/25/25 mbar |

CONNECTIONS TECHNICAL SPECIFICATIONS

| | |
|----------------|-------|
| Gas diameter 1 | R3/4" |
|----------------|-------|