



**Catalogue**  
FOOD SERVICE  
**Chapter**  
COOKING

**Specific model**  
FT-G905 L NG 230V 1N

19101451

30/05/2023

**DENOMINATION:**

GN gas frytop with thermostatic temperature control, smooth hot-plate, half module, 900 range.


**DESCRIPTION :**

- Surface tops manufactured in 2 mm thick AISI-304 stainless steel.
- Laser-cut joints, automatic welding and polishes. Screws hidden from view.
- Fry-tops manufactured in 20 mm thick mild steel, high powered and with rapid temperature attainment.
- Rapid reaction and recovery times of the fry-top temperature.
- The fry-tops are integrated into the funnelled surface top.
- The funnelled housing with rounded edges and corners make them very easy to clean.
- Fry-top tilted towards the front to facilitate fat and liquid collection.
- Fitted with an opening for the collection of cooking fat and storage tray with a capacity of up to 2 litres depending on the model.
- Option of easily dismountable side and back splash guards.
- High temperature enamelled cast iron flue protector.
- Access to the components from the front.
- Machines with IPX5 grade water protection.
- Smooth hot-plate.
- "- Gas heated model with burners with two branches.
- Thermostatic temperature control (between 100 and 300 °C).
- Ignition by electronic spark train. Have access tube for manual ignition.
- "

**POSSIBLE ACCESSORIES :**

- STANDS 900
- ACCESSORIES KORE
- FRY-TOP ACCESSORIES KORE
- TALL CHIMNEY KORE

**DIMENSIONS**



|            |          |                |          |
|------------|----------|----------------|----------|
| X Width    | 400 mm   | X Gross width  | 440 mm   |
| Y Depth    | 930 mm   | Y Gross depth  | 1022 mm  |
| Z Height   | 290 mm   | Z Gross height | 535 mm   |
| Net Weight | 70,0 kg  | Gross Weight   | 88,0 kg  |
| Net volume | 0,110 m3 | Gross volume   | 0,241 m3 |

**ELECTRICITY TECHNICAL SPECIFICATIONS**

|                    |           |
|--------------------|-----------|
| Electric power     | 0,100 kW  |
| Amperage (A)       | 2A        |
| Voltage            | 230V - 1N |
| Electric frequency | 50/60Hz   |

**GAS TECHNICAL SPECIFICATIONS**

|                 |                                |
|-----------------|--------------------------------|
| Gas type        | NG                             |
| Gas power       | 9,25 kW                        |
| Gas consumption | 0,978 m3/h                     |
| Regulated       | NG G20/G25/G25.1 20/25/25 mbar |

**CONNECTIONS TECHNICAL SPECIFICATIONS**

|                |       |
|----------------|-------|
| Gas diameter 1 | R3/4" |
|----------------|-------|