

# DENOMINATION:

Electric cooker with oven, 6 square plates, 900 range.

# **DESCRIPTION :**

- "- Surface tops manufactured in 2 mm thick AISI-304 stainless steel, designed to prevent liquids spilt from the pans from penetrating into the cooker.
- Laser-cut joints, automatic welding and polishes. Screws hidden from view.
- Hot plates manufactured with 300 x 300 mm cast iron, with 4 kW of

"- Easy to use static oven with dimensions 1,000 x 700 x 290 mm (OP version cookers), with the controls positioned on the upper panel.

- Easy to use static GN 2/1 size oven with the controls positioned on

- Cooking chamber constructed entirely in stainless steel, making it

- Heating by means of stainless steel shielded heating elements with

- Fibreglass closing seal to improve the oven's thermal efficiency.

- power, hermetically sealed into the funnelled surface top.
- Power regulation by 7 position selector.
- Safety thermostat for each plate.
- Interior fan to lower the temperature of the components.
- Funnelled surface with rounded corners for easy cleaning.
- High temperature enamelled cast iron flue protector.
- Access to the components from the front.

the upper panel for better ergonomics.

performance and even heat distribution.

easier to clean and providing better hygiene.
Tray introduced sideways for easier handling.
Guides at three heights to offer different working options.
Guides with "U" shape to prevent the trays from tipping.
Thermostatic temperature control (125 – 310 °C).

- Machines with IPX5 grade water protection.
- VOLTAGE: 400 V 3+N. Ask for other voltages

- Catalogue FOOD SERVICE Chapter COOKING

Specific model C-E961 OP 400V 3N

19075516

DIMENSIONS

11/11/2021

X Width	1200	mm	X Gross width	1240	mm
Y Depth	930	mm	Y Gross depth	1022	mm
Z Height	850	mm	Z Gross height	1255	mm
Net Weight	150,0	kg	Gross Weight	172,0	kg
Net volume	0.950	m3	Gross volume	1.590	m3

### ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	36,000 kW
Amperage (A)	63A
Heating power	36,00 kW
Voltage	400V - 3N
Electric frequency	50/60Hz
CONNECTIONS TECHNICAL SPECIFICATIONS	

Three-phase +N 400V wiring

3X10MM2+T+N

- 230 1N- Transformation A 230 V single phase

- Dismountable oven door to facilitate repair. "

- 230 III - A 230 V three-phase transformation without neutral

selector switch to operate the upper and/or lower zone. - Oven floor manufactured in 6 mm cast iron, guaranteeing better

- MARINE - Other machines - Ship transformation - 440 III

#### **POSSIBLE ACCESSORIES :**

- ACCESSORIES KORE

**POSSIBLE OPTIONS :** 

- COOKER ACCESSORIES KORE
- KORE WHEELS
- TALL CHIMNEY KORE

# SUPPLIED ACCESSORIES:

- 19040900 Door kit for Kore stands 1



www.fagorprofessional.com





Catalogue FOOD SERVICE

Capítulo COOKING

Modelo C-E961 OP 400V 3N

19075516

11/11/2021







C-E961 OP



E. Conexión eléctrica
1. Mando placas M
2. Mando horno 1
3. Mando horno 2

()) ()) ()) Electrical connection M plates control Oven control 1 Oven control 2 E

www.fagorprofessional.com