# product sheet updated 02/12/2024











(PrecisePulse function).

 $\checkmark$  Option to customize programs for recipe standardization.

#### **Built to last**

Made from stainless steel and food-grade materials of the highest quality: stainless steel motor block and food-grade aluminium head. Stainless steel hopper with highly-resistant lid.

#### Maximum comfort for the user

- Ergonomic design: product sliced in one single movement.
- Lateral product output: it requires less room on the work surface and directs the product avoiding splashing.
- Advanced control panel that is very intuitive to use and offers all the information at a glance.

#### Maintenance, safety, hygiene

- Plunger, lid and bowl easy to remove for changing or cleaning.
- ✓ Combination of security systems: head, covers, bowl, power switch.
- Appliance certified by NSF International (regulations on hygiene, cleaning and materials suitable for contact with foods).
- √ 100% tested.

### NCLUDES

- ✓ Variable speed motor block.
- ✓ Universal head.
- Cutter bowl, with micro-serrated blade rotor.
- √ Universal grid cleaner QC-U.

#### **O**PTIONAL

☐ Tube head.

blades.

- Discs, grids and disc support.Rotor with smooth cutting
- Rotor with perforated cutting blades.
- □ Support-trolley.□ Grid cleaning kit.

#### Accessories

- ☐ FCC curved slicing discs
- $\hfill \square$  FCO rippled slicing discs
- ☐ FFC chipping grids
- ☐ FMC dicing grids
- ☐ FCE julienne discs
- ☐ Disc and grid packs Heavy
- ☐ Disc and grid holder
- ☐ Blades for CK / K / KE
- ☐ Quick Cleaner: grid cleaners
- □ FC-D slicing discs
- ☐ SH shredding & grating discs

#### **SPECIFICATIONS**

Total loading: 1500 W

#### As vegetable preparation machine

Hourly production: 100 kg - 450 kg

Inlet opening: 136 cm<sup>2</sup> Disc diameter: 205 mm

Speed as veg. slicer: 300 rpm - 1000 rpm

External dimensions (W x D x H): 391 mm x 409 mm x 552 mm

Net weight (Veg.Prep.):24 kg

#### As cutter

Bowl capacity: 5.5 l

Speeds as cutter (positions): 300 rpm - 3000 rpm

External dimensions (W x D x H):286 mm x 387 mm x 487 mm

Net weight (Cutter): 18 kg Noise level (1m.): <70 dB(A) Background noise: 32 dB(A)

Crated dimensions 705 x 415 x 515 mm Volume Packed: 0.15 m³ Gross weight: 31.8 kg

# SALES DESCRIPTION

It has a variable speed motor block, universal head and 5.5 I cutter bowl equipped with a rotor with micro-serrated blades.

"Brushless" technology.

## Equipped with "brushless" technology: powerful and efficient motors.

- ✓ Maximum efficiency: maintain the torque throughout the speed
- Exclusive "force control system": guarantee of a uniform and high quality result.
- √ Lightweight and compact design: they weigh less, they occupy less snace.
- √ Improved air/water-tightness since no ventilation is required.
- √ They generate less noise: improved workplace environment.

#### Cutting function: a perfect cut

- High precision settings and comprehensive cutter and disc design aimed at obtaining a perfect cut.
- ✓ It can be fitted with a wide range of discs and grids of the highest cutting quality. By combining these accessories, you can achieve more than 70 different types of cuts and grating grades.
- Exclusive "Force Control System" to optimise and standardise the cutting of each product: acoustic warning when the motor exceeds the pre-established force.

#### Cutter function: efficiency and performance

- √ Possibility of programming by time and pulse button.
- √ Reverse function, ideal for mixing products instead of cutting.
- √ 5.5 lt stainless steel bowl.
- ✓ Transparent lid with built-in "cut&mix" mixer.
- Depending on the purpose, the possibility of using optional smooth or perforated blades.
- Built-in parametrisable programs to obtain the desired texture in seconds and in a standardized way: dense texture, fine texture, pulses







# updated 02/12/2024 product sheet







#### **AVAILABLE MODELS**


1050752 Combi vegetable prep.-cutter CK-35V 230/50-60/1


1050756 Combi vegetable prep.-cutter CK-35V 120/50-60/1

\* Ask for special versions availability











Polígono Basarte, 1. 20720 Azkoitia, Spain phone +34 943 15 72 36 sales@sammic.com



Project	Date
Item	Qty

Approved