



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
MUP-11G GD LC 230V 1N 50Hz

19089440

17/07/2024

The photo may show the standard model and not the configured one

DENOMINATION:

Concept Monoblock GN 2/1 refrigeration upright, single body with 1 glass door, with lock.

DESCRIPTION :

- Interior constructed with AISI-304 stainless steel exterior in food grade stainless steel.
- 60 mm thickness, CFC-free, high-density (40 kg/m³) polyurethane insulation, injected under high pressure.
- Embedded inner guides with 23 different level position 55 mm distance among them, enable more convenient cleaning operations without difficulties.
- Intuitive, digital display for electronic control with energy saving function to ensure an optimal control of storing products.
- Removable pull-out/push-in magnetic door gasket to keep maximum hygiene and maintain the insulating properties.
- Hinged doors with automatic return for a perfect closing that minimize temperature gain. Doors have a 120° dwell position and close automatically at less than 90°.
- Pivotal panel with better access to control that facilitates service, thus enlarging the useful life of the equipment.
- Automatic evaporation of defrost water.
- Internally designed monoblock cooling system. Top mounted evaporator ensure an easy maintenance of refrigeration unit, as well as an optimized use of storage compartment.
- Optimal air circulation system that guarantees a balanced and constant distribution throughout the equipment, so that the temperature remains uniform. It helps preserve food for longer.
- Height-adjustable stainless steel legs. Height of the legs can be adjusted individually (130 mm - 200 mm) to enable convenient cleaning.
- Low energy consumption LED lighting vertically located in the interior of compartment.
- Stamped edge interiors, for easier cleaning operations to reduce potential dirt traps with a built-in drainage to get rid of waste liquid inside units.
- Removable and height adjustable epoxy coated GN 2/1 grids with a maximum loading capacity of up to 40 kg.
- Suitable for 1 x GN2/1 or 2 x GN1/1 food containers.
- Double-glazed doors insulated with low thermal emissivity to reduce heat transfer in refrigeration.
- Defrost by compressor stop.
- Equipped with 3 GN2/1 grid per each full door.


POSSIBLE OPTIONS :

- 60 Hz
- Stainless Backing
- Wheels Kit (Factory Assembly)
- Door frame resistance
- Opposite Opening
- Pedal
- Remote group

STANDARD OPTIONS :

- Glass door
- Locks

DIMENSIONS



X Width	653 mm	X Gross width	730 mm
Y Depth	796 mm	Y Gross depth	880 mm
Z Height	1996 mm	Z Gross height	2017 mm
Net Weight	149,0 kg	Gross Weight	156,0 kg
Net volume	1,037 m ³	Gross volume	1,296 m ³

ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	0,146 kW
Voltage	230V
Phases	1N
Electric frequency	50Hz
Amperage (A)	0,6 A

COLD TECHNICAL SPECIFICATIONS

Temperature	0 +8 °C
Climate class	4
Refrigeration power	0,274 kW
GWP	3
Cooling gas load	95,000 g
Gross internal volume	572 L
Noise level	53,00 dB
Condensation system	Vent.

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1+T-2A
--------------------------	----------

OTHERS

Number of doors	1
-----------------	---





Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
MUP-11G GD LC 230V 1N 50Hz

19089440

17/07/2024

The photo may show the standard model and not the configured one

POSSIBLE ACCESSORIES :

- ACCESSORIES FOR REFRIGERATION
- GASTRONORM GRIDS

SUPPLIED ACCESSORIES:

- 19097787 GN 2/1 epoxi grid for GN 2/1 refrigerated upright. 3



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
MUP-11G GD LC 230V 1N 50Hz

19089440

17/07/2024

