



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CUP-11G1/1 GD LC 230V 1N 50Hz

19089487

17/07/2024

The photo may show the standard model and not the configured one

DENOMINATION:

Concept gastronorm GN 1/1 refrigerated upright, single body with 1 glass door.

DESCRIPTION :

- Interior constructed with AISI-304 stainless steel exterior in food grade stainless steel.
- 60 mm thickness, CFC-free, high-density (40 kg/m³) polyurethane insulation, injected under high pressure.
- Removable guiding rails construction with 18 grid level position per each full door with 70 mm distance among them.
- Intuitive, digital display for electronic control with energy saving function to ensure an optimal control of storing products.
- Removable pull-out/push-in magnetic door gasket to keep maximum hygiene and maintain the insulating properties.
- Hinged doors with automatic return for a perfect closing that minimize temperature gain. Doors have a 120° dwell position and close automatically at less than 90°.
- Pivotable panel with better access to control that facilitates service, thus enlarging the useful life of the equipment.
- Automatic evaporation of defrost water.
- Internally designed forced draft cooling system with low consumption electronic components to guarantee optimal equipment efficiency and performance.
- Optimal air circulation system that guarantees a balanced and constant distribution throughout the equipment, so that the temperature remains uniform. It helps preserve food for longer.
- Height-adjustable stainless steel legs. Height of the legs can be adjusted individually (130 mm - 200 mm) to enable convenient cleaning.
- Low energy consumption LED lighting horizontally located in the interior of compartment.
- Stamped edge interiors, for easier cleaning operations to reduce potential dirt traps with a built-in drainage to get rid of waste liquid inside units.
- Removable and height adjustable epoxy coated GN 1/1 grids with a maximum loading capacity of up to 40 kg.
- Double-glazed doors insulated with low thermal emissivity to reduce heat transfer in refrigeration.
- Defrost by compressor stop.

POSSIBLE OPTIONS :

- 60 Hz
- Stainless Backing
- Wheels Kit (Factory Assembly)
- Door frame resistance
- Opposite Opening
- Remote group


STANDARD OPTIONS :

- Glass door
- Locks

POSSIBLE ACCESSORIES :

- ACCESSORIES FOR REFRIGERATION

DIMENSIONS



X Width	490 mm	X Gross width	770 mm
Y Depth	700 mm	Y Gross depth	565 mm
Z Height	2010 mm	Z Gross height	2050 mm
Net Weight	102,0 kg	Gross Weight	115,0 kg
Net volume	1,122 m ³	Gross volume	0,892 m ³

ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	0,208 kW
Voltage	230V
Phases	1N
Electric frequency	50Hz
Amperage (A)	1 A

COLD TECHNICAL SPECIFICATIONS

Temperature	0 +8 °C
Climate class	4
Refrigeration power	0,361 kW
GWP	3
Cooling gas load	100,000 g
Noise level	53,00 dB
Condensation system	Vent.
Model Type	1 refrigeration comp equipment
Annual elec. consumption	1197,90 kWh
Power consumption 24h	3,28 kWh
Energy efficiency Index (EEI)	21,3
Clasif. Energy efficiency	C

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1+T-2A
--------------------------	----------

OTHERS

Number of doors	1
-----------------	---





Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CUP-11G1/1 GD LC 230V 1N 50Hz

19089487

17/07/2024

The photo may show the standard model and not the configured one

- GASTRONORM GRIDS

SUPPLIED ACCESSORIES:

- 19097778 GN 1/1 epoxy grid for GN 1/1 refrigerated upright. 3
- 19100845 Tray support guides for GN 1/1 refrigerated upright. 3



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CUP-11G1/1 GD LC 230V 1N 50Hz

19089487

17/07/2024

