



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
AUPT-22G LC 230V 1N 50Hz

19103142

16/07/2024

The photo may show the standard model and not the configured one

DENOMINATION:

Advance gastronorm GN 2/1 refrigerated upright, double body with 2 doors.


DESCRIPTION :

- Interior and exterior completely built with AISI-304 stainless steel.
- 80 mm thickness, CFC-free, high-density (40 kg/m³) polyurethane insulation, injected under high pressure.
- Embedded inner guides with 24 different level position 55 mm distance among them, enable more convenient cleaning operations without difficulties.
- Intuitive, large digital display for electronic control with energy saving function to ensure an optimal control of storing products.
- 10 HACCP alarms capacity which are store when high temperature variation and devices power failure.
- Removable pull-out/push-in magnetic door gasket to keep maximum hygiene and maintain the insulating properties.
- Hinged doors with automatic return for a perfect closing that minimize temperature gain. Doors have a 120° dwell position and close automatically at less than 90°.
- Pivotal panel with better access to control that facilitates service, thus enlarging the useful life of the equipment.
- Automatic evaporation of defrost water.
- Internally designed forced draft cooling system with low consumption electronic components to guarantee optimal equipment efficiency and performance.
- Optimal air circulation system that guarantees a balanced and constant distribution throughout the equipment, so that the temperature remains uniform. It helps preserve food for longer.
- Height-adjustable stainless steel legs. Height of the legs can be adjusted individually (95 mm - 115 mm) to enable convenient cleaning.
- Low energy consumption LED lighting vertically located in the interior of compartment.
- Equipped with a door lock in full door models.
- Stamped edge interiors, for easier cleaning operations to reduce potential dirt traps with a built-in drainage to get rid of waste liquid inside units.
- Removable and height adjustable epoxy coated GN 2/1 grids with a maximum loading capacity of up to 40 kg.
- Suitable for 1 x GN2/1 or 2 x GN1/1 food containers.
- Stainless steel doors with ergonomic, full-length, robust, perfectly integrated handle. that ensures practical opening and avoids dust and dirt collection.
- Defrost by a heating element to remove ice accumulated in the evaporator.
- Equipped with 3 GN2/1 grid per each full door and a set of grid support guides for middle beam.

POSSIBLE OPTIONS :

- Stainless Backing
- Wheels Kit (Factory Assembly)
- Door frame resistance
- Connectivity
- Pedal
- Remote group

DIMENSIONS



X Width	1358 mm	X Gross width	1430 mm
Y Depth	856 mm	Y Gross depth	880 mm
Z Height	2106 mm	Z Gross height	2185 mm
Net Weight	227,0 kg	Gross Weight	240,0 kg
Net volume	2,371 m ³	Gross volume	2,750 m ³

ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	0,972 kW
Voltage	230V
Phases	1N
Electric frequency	50Hz
Amperage (A)	3,2 A

COLD TECHNICAL SPECIFICATIONS

Temperature	-2 +8 °C
Refrigeration power	0,436 kW
GWP	3
Cooling gas load	103,000 g
Gross internal volume	1332 L
Noise level	53,00 dB
Condensation system	Vent.

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1+T-2A
--------------------------	----------





Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
AUPT-22G LC 230V 1N 50Hz

19103142

16/07/2024

The photo may show the standard model and not the configured one

STANDARD OPTIONS :

- Locks

POSSIBLE ACCESSORIES :

- ACCESSORIES FOR REFRIGERATION
- GASTRONORM GRIDS

SUPPLIED ACCESSORIES:

- 19014778 Tray support guides for GN 2/1 double body upright. 3
- 19097787 GN 2/1 epoxi grid for GN 2/1 refrigerated upright. 6



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
AUPT-22G LC 230V 1N 50Hz

19103142

16/07/2024

