sammic

VACUUM SEALER SU-416

Tabletop model. 16 m³/h. 420 mm.





Sales Description

420 mm sealing bar. 16 m³/h Busch vacuum pump. Vacuum controlled by sensor.

- √ Powered by Busch.
- √ Vacuum controlled by sensor.
- √ Vacuum PLUS.
- ✓ LCD colour screen: all information at a glance.
- √ Backlit touch keyboard.
- √ Programmable: 99-programme memory. Blocking option.
- ✓ "Pause" button to marinate food.
- ✓ Phased vacuum programme.
- ✓ Detection of the evaporation of liquids.
- ✓ Double seal.
- √ Cordless sealing bar.
- √ Bag sealing program.
- √ Progressive decompression.
- \checkmark Vac-Norm ready with automatic decompression.
- √ Stainless steel body and chamber. Deep-drawn chamber.
- ✓ Damped transparent lid.
- Dry-oil programme for drying the pump.
- Working hours counter for oil changes.
- ✓ Safety system with protection against vacuum failure.

INCLUDES

- ✓ Busch pump.
- ✓ Sensor controls.
- Programmable.
- ✓ Bluetooth connectivity.
- √ Vacuum plus: up to 10 seconds of extra vacuum pull.
- ✓ Soft air function.

- √ Clear methacrylate lid.
- ✓ Pause function.
- ✓ Liquid detection system.
- ✓ Dry oil cycle.
- √ NSF approved.
- √ Filling plate.

OPTIONAL

- Inert gas.
- Printer.
- Vacuum packing bags.
- ☐ External vacuum kit for Vac-Norm, containers and
- accessories.
- Bag cutting kit.
- ☐ Support for liquid packaging.
- Additional filling plates.

ACCESSORIES

- Bag cutting kits
- Filling plates
- □ Liquid insert plates□ Vac-norm external vacuum kit
- Vac-norm containers
- Smooth bags for vacuum packing
- ☐ Trolley for vacuum packing machines
- ☐ Thermal labels for CG2 / RB printer
- RB desktop printer for SU vacuum packing machines
- ☐ Thermal transfer labels for RB printer

SPECIFICATIONS

Pump capacity: 16 m³/h

Pump capacity (60 Hz): 19 m³/h

Bar length: 420 mm Total loading: 550 W

Vacuum pressure (maximum): 2 mbar

Internal dimensions

- √ Width: 430 mm
- ✓ Depth: 415 mm
- ✓ Height: 180 mm

External dimensions (W x D x H)

- √ Width: 484 mm
- √ Depth: 529 mm
- √ Height: 448 mm (230V) / 529 mm (120V)

Noise level (1m.): 75 dB(A) Background noise: 32 dB(A)

Crated dimensions 600 x 600 x 610 mm







VACUUM SEALER SU-416 Tabletop model. 16 m³/h. 420 mm.

AVAILABLE MODELS

	1140762	SU-416P 230/50-60/1
	1140763	SU-416GP 230/50-60/1
	1140767	SU-416P 120/50-60/1
	1140768	SU-416GP 120/50-60/1
	1140770	SU-416GP+ 120/50-60/1
	1140728	SU-416GP 230/50-60/1 AUS
	1141092	SU-416GP+ 100/50-60/1
	1141094	SU-416P+ 100/50-60/1

^{*} Ask for special versions availability

Polígono Basarte, 1. 20720 Azkoitia, Spain phone +34 943 15 72 36 sales@sammic.com



Item Qty	Project	Date
	Item	Qty

Approved

	N
	(Q)
	_
	a
	-
eet	
A.	_
Ψ	м
-	
sh	- 24
	100
α	\sim
м	ぶ
	Ψ.
~	⇟
v	·(υ
	$\overline{}$
9	$\overline{}$
5	