



Catalogue

FOOD SERVICE

Chapter

REFRIGERATION

Specific model

UN-251

19089738 08/07/2024

The photo may show the standard model and not the configurated one

DENOMINATION:

Professional freezer maintenance cabinet with 2 shelves.

DESCRIPTION:

- Exterior finishing: White coated galvanized steel.
- Removable pull-out/push-in magnetic door gasket to keep maximum hygiene and maintain the insulating properties
- Hinged doors with automatic return for a perfect closing that minimize temperature gain. Doors have a 120° dwell position and close automatically at less than $90^\circ.$
- CFC-free, high-density (40 kg/m³) polyurethane insulation, injected under high pressure.
- Rounded edge interiors, for easier cleaning operations to reduce potential dirt traps with a built-in drainage to get rid of waste liquid inside units.
- Intuitive, digital display for electronic control with energy saving function to ensure an optimal control of storing products.
- ON/OFF power switch.
- Door designed for easy opening orientation modification.
- Interior construced with white coated galvanized steel.
- Doors with ergonomic, full-length, robust, perfectly integrated handle. that ensures practical opening and avoids dust and dirt collection
- Internally designed forced draft cooling system with the evaporator integrated in the back side of the upright guarantees optimal cold distribution, efficiency and performance.
- Optimal air circulation system that guarantees a balanced and constant distribution throughout the equipment, so that the temperature remains uniform. It helps preserve food for longer.

POSSIBLE OPTIONS:

- 60 Hz
- Wheels Kit (Factory Assembly)

<u>DIMENSIONS</u>				×		
				Y		
X Width	626	mm	X Gross width	715	mm	
Y Depth	600	mm	Y Gross depth	647	mm	
Z Height	850	mm	Z Gross height	975	mm	
Net Weight	51,0	kg	Gross Weight	54,0	kg	
Net volume	0,391	m3	Gross volume	0,451	m3	
ELECTRICITY TECHNICAL SPECIFICATIONS						
LLLOTRIOTT TEOTIN	OAL OI L	JII 101	ATIONO			
Electric power				0,14	2 kW	

Electric power	0,142 kW
Voltage	230V
Phases	1N
Electric frequency	50Hz
Amperage (A)	1,1A

COLD HORECA ECO LABEL	
Termperature	-22 -15 °C
Climate class	4
Refrigeration power	0,218 kW
Gas type	R-290
GWP	3
Cooling gas load	38,000 g
Gross internal volume	125 L

Noise level 43,00 dB
Condensation system Static

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring 2X1,5+T - 6 A















Catalogue

FOOD SERVICE

Chapter

REFRIGERATION

Specific model

UN-251

19089738 08/07/2024











