

		SR-2-11 TP2		SR-2-14 TP2		SR-2-18 TP2	
CAPACITY							
Capacity 1/18	Kg	11,7 x 2		15 x 2		18,3 x 2	
	Lb	25,7 x 2		33,1		40,4	
Capacity 1/20	Kg	10,5 x 2		13,5 x 2		16,5 x 2	
	Lb	23,1 x 2		29,8		36,3	
DRUM							
Ø Drum	mm	750		750		750	
	inch	29,53		29,53		29,53	
Drum length	mm	475		610		746	
	inch	18,7		24,02		29,37	
Drum volume	l	210		270		330	
	cu ft	7,41		9,53		11,64	
Ø Door	mm	574		574		574	
	inch	22,6		22,6		22,6	
Floor to door center	mm	547 / 1522		547 / 1522		547 / 1522	
	inch	21,54 / 59,92		21,54 / 59,92		21,54 / 59,92	
Floor to lower part of the door	mm	189 / 1164		189 / 1164		189 / 1164	
	inch	7,32 / 45,83		7,32 / 45,83		7,32/45,83	
Drum motor power	kW	0,37 x 2		0,37 x 2		0,37 x 2	
ELECTRIC POWER							
Installed heating power	Kw	12 x 2		12 x 2		1,12 x 2	
Installed electrical power	Kw	25,34		25,34		25,34	
Evaporation capacity	l/h	15,8		17,2		18,1	
	USgallon/h	4,17		4,54		4,78	
Hourly output	Kg/h	31,6		34,4		36,2	
	Lb/h	69,7		75,8		79,8	
GAS POWER							
Installed heating power gas	kcal/h	10327 x 2		10327 x 2		10327 x 2	
	Btu/h	40945.7 x 2		40945.7 x 2		40945.7 x 2	
Installed heating power gas	kW	12 x 2		12 x 2		12 x 2	
Installed electrical power	Kw	1,34		1,34		1,34	
Instant propane gas consumption (G31)	Kg/h	1,03 x 2		1,03 x 2		1,03 x 2	
	Lb/h	2,27 x 2		2,27 x 2		2,27 x 2	
Instant natural gas consumption (G20)	m³/h	1,27 x 2		1,27 x 2		1,27 x 2	
	cfm	0,75 x 2		0,75 x 2		0,75 x 2	
Evaporation capacity	l/h	15,3		16,9		18	
	USgallon/h	4,042		4,465		4,755	
Hourly output	Kg/h	30,6		33,8		36	
	Lb/h	67,5		74,5		79,4	
Ø Gas inlet	BSPP ISO 228-1	1/2"		1/2"		1/2"	
VENTILATION							
Nominal air flow	m³/h	500 x 2		500 x 2		500 x 2	
	cfm	294,28 x 2		294,28 x 2		294,28 x 2	
Air outlet Ø	mm	200		200		200	
	inch	7,87		7,87		7,87	
Fan motor power	kW	0,25 x 2		0,25 x 2		0,25 x 2	
HEAT DISSIPATION							
Total max heat dissipation	kW	2,4		2,4		2,4	
	Btu/h	8193,9		8193,9		8193,9	
Front pannel max heat dissipation	kW	1,68		1,68		1,68	
	Btu/h	5735,8		5735,8		5735,8	
CONNECTIONS		ELECTRICAL	GAS	ELECTRICAL	GAS	ELECTRICAL	GAS
Tension 230V - I + N + T	Nº x mm2 / A	-	3x1.5 A / 16	-	3x1.5 A / 16	-	3x1.5 A / 16
Tension 230V - III + T	Nº x mm2 / A	4 x 25 A / 80	3x1.5 A / 16	4 x 25 A / 80	3x1.5 A / 16	4 x 25 A / 80	3x1.5 A / 16
Tension 400V - III + N + T	Nº x mm2 / A	5 x 10 A / 40	3x1.5 A / 16	5 x 10 A / 40	3x1.5 A / 16	5 x 10 A / 40	3x1.5 A / 16