



FINISHING

SPOTTING TABLES DES-COMPLET / COMPACT



DES-COMPLET



DES-COMPACT

CHARACTERISTICS

DES-COMPLET

- Cold spotting table with built-in suction unit.
- Cold spotting table.
- Featuring two cold spotting spray guns with independent circuits, two receptacles for liquids, hose support and swinging arm with suction and spotting shape out of stainless steel AISI 304.
- Board out of stainless steel AISI 304.
- Board dimensions: de 800 x 260 x 175 mm.
- Electric connection: 230V I+N / 50-60 Hz.
- With compressor: 230/400V III 50Hz.
- It needs compressed air (200 NI/min).

DES-COMPACT

- Cold spotting table with built-in suction unit.
- Equipped with two receptacles for liquids and one spotting spray gun.
- One working pedal.
- Electric connection: 230V I+N / 50-60 Hz.
- It needs compressed air.

OPTIONS

- Compressor for DES-COMPLET.
- Air-steam gun for DES-COMPLET.
- Trolley for DES-COMPACT.

TECHNICAL DATA

SPOTTING TABLES | DES-COMPLET / COMPACT

| | UNIT. | DES-COMPLET | DES-COMPACT |
|--|----------------|--|----------------|
| GENERAL DETAILS | | | |
| Board dimensions | mm | 800 x 260 x 175 | 400 x 200 x 35 |
| Boiler | - | No | No |
| Boiler capacity | l | - | - |
| Compressor | - | Opt | - |
| Group of Iron | - | - | - |
| Steam gun | - | Opt | - |
| Polished upper buck | - | - | - |
| POWER | | | |
| Vacuum Motor | HP | 0,6 | 0,13 |
| Pump Motor | HP | - | - |
| Compressor motor (Mod. with option) | HP | 2 | - |
| Boiler Heater (Mod. with option) | kW | - | - |
| Fan motor | kW | - | - |
| CONNECTIONS | | | |
| Ø Water inlet | BSP | - | - |
| Ø Boiler exhaust (mod. with boiler) | BSP | - | - |
| Ø Steam inlet | BSP | 3/8" | - |
| Ø Condensate outlet | BSP | 3/8" | - |
| Steam pressure | BAR | 4,5 | - |
| Steam Consumption | Kg/h | 2-3 | - |
| Ø Air inlet | BSP | 1/4" | 1/4" |
| Ø Air outlet | mm | 90 | - |
| Air pressure | BSP | 4-8 | 6-8 |
| Air Consumption | NI/m | 200 | 30 |
| DIMENSIONS / PACKING DIMENSIONS | | | |
| Width / Width | mm | 1.200/1.300-1.340 (Wooden box) | 640/600 |
| Depth / Depth | mm | 650/540-960 (Wooden box) | 320/450 |
| Height / Height | mm | 1.800/1.160-1.170 (Wooden box) | 325-670/540 |
| Net weight / Gross weight | kg | 44 / 78 (+compres.)/58-145 (+compres.) | 13/16 |
| Volume | m ³ | 1,40/1,51 | 0,14/0,15 |
| OTHERS | | | |
| Voltage | Hz | 230V 50/60 | 230V 50/60 |
| Sound level | dB | 65 | 65 |