



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CUP-22G 230V 1N 50Hz

19089448

17/07/2024

The photo may show the standard model and not the configured one

DENOMINATION:

Concept gastronorm GN 2/1 refrigerated upright, double body with 2 doors.

DESCRIPTION :


- Interior constructed with AISI-304 stainless steel exterior in food grade stainless steel.
- 60 mm thickness, CFC-free, high-density (40 kg/m³) polyurethane insulation, injected under high pressure.
- Embedded inner guides with 23 different level position 55 mm distance among them, enable more convenient cleaning operations without difficulties.
- Intuitive, digital display for electronic control with energy saving function to ensure an optimal control of storing products.
- Removable pull-out/push-in magnetic door gasket to keep maximum hygiene and maintain the insulating properties.
- Hinged doors with automatic return for a perfect closing that minimize temperature gain. Doors have a 120° dwell position and close automatically at less than 90°.
- Pivotal panel with better access to control that facilitates service, thus enlarging the useful life of the equipment.
- Automatic evaporation of defrost water.
- Internally designed forced draft cooling system with low consumption electronic components to guarantee optimal equipment efficiency and performance.
- Optimal air circulation system that guarantees a balanced and constant distribution throughout the equipment, so that the temperature remains uniform. It helps preserve food for longer.
- Height-adjustable stainless steel legs. Height of the legs can be adjusted individually (125 mm - 200 mm) to enable convenient cleaning.
- Low energy consumption LED lighting vertically located in the interior of compartment.
- Stamped edge interiors, for easier cleaning operations to reduce potential dirt traps with a built-in drainage to get rid of waste liquid inside units.
- Removable and height adjustable epoxy coated GN 2/1 grids with a maximum loading capacity of up to 40 kg.
- Suitable for 1 x GN2/1 or 2 x GN1/1 food containers.
- Stainless steel doors with ergonomic, full-length, robust, perfectly integrated handle. that ensures practical opening and avoids dust and dirt collection.
- Defrost by compressor stop.
- Equipped with 3 GN2/1 grid per each full door and a set of grid support guides for middle beam.

POSSIBLE OPTIONS :

- 60 Hz
- Stainless Backing
- Wheels Kit (Factory Assembly)
- Door frame resistance
- Locks
- Pedal
- Remote group

POSSIBLE ACCESSORIES :

DIMENSIONS



| | | | |
|------------|----------------------|----------------|----------------------|
| X Width | 1318 mm | X Gross width | 1430 mm |
| Y Depth | 842 mm | Y Gross depth | 880 mm |
| Z Height | 2040 mm | Z Gross height | 2063 mm |
| Net Weight | 227,0 kg | Gross Weight | 240,0 kg |
| Net volume | 2,264 m ³ | Gross volume | 2,596 m ³ |

ELECTRICITY TECHNICAL SPECIFICATIONS

| | |
|--------------------|----------|
| Electric power | 0,206 kW |
| Voltage | 230V |
| Phases | 1N |
| Electric frequency | 50Hz |
| Amperage (A) | 0,84 A |

COLD TECHNICAL SPECIFICATIONS

| | |
|---------------------------|------------------|
| Temperature | 0 +8 °C |
| Climate class | 4 |
| Refrigeration power | 0,436 kW |
| GWP | 3 |
| Cooling gas load | 100,000 g |
| Gross internal volume | 1186 L |
| Noise level | 53,00 dB |
| Condensation system | Vent. |
| Model Type | Vertical cabinet |
| Annual elec. consumption | 913,00 kWh |
| Power consumption 24h | 2,50 kWh |
| Refrigeration net.vol | 859 L |
| IEE | 45 |
| Clasif. Energy efficiency | C |

CONNECTIONS TECHNICAL SPECIFICATIONS

| | |
|--------------------------|----------|
| Single-phase 230V wiring | 2X1+T-2A |
|--------------------------|----------|

OTHERS

| | |
|-----------------|---|
| Number of doors | 2 |
|-----------------|---|





Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CUP-22G 230V 1N 50Hz

19089448

17/07/2024

The photo may show the standard model and not the configured one

- ACCESSORIES FOR REFRIGERATION
- GASTRONORM GRIDS

SUPPLIED ACCESSORIES:

- 19014778 Tray support guides for GN 2/1 double body upright. 3
- 19097787 GN 2/1 epoxi grid for GN 2/1 refrigerated upright. 6



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CUP-22G 230V 1N 50Hz

19089448

17/07/2024

