



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CUD-22G/M FH 230V 1N 50Hz

19089470

17/07/2024

The photo may show the standard model and not the configured one

DENOMINATION:

Concept gastronorm GN 2/1 dual temperature upright, double body with 2 doors.

DESCRIPTION :

- Interior constructed with AISI-304 stainless steel exterior in food grade stainless steel.
 - 60 mm insulation, embedded and inner guides independent modules with their respective refrigeration units and electronic controls.
 - Intuitive, digital display for electronic control with energy saving function to ensure an optimal control of storing products.
 - Stainless steel doors with ergonomic, full-length, robust, perfectly integrated handle. that ensures practical opening and avoids dust and dirt collection.
 - Removable pull-out/push-in magnetic door gasket to keep maximum hygiene and maintain the insulating properties.
 - Hinged doors with automatic return for a perfect closing that minimize temperature gain. Doors have a 120° dwell position and close automatically at less than 90°.
 - Pivotal panel with better access to control that facilitates service, thus enlarging the useful life of the equipment.
 - Automatic evaporation of defrost water.
 - Internally designed forced draft cooling system with low consumption electronic components to guarantee optimal equipment efficiency and performance.
 - Optimal air circulation system that guarantees a balanced and constant distribution throughout the equipment, so that the temperature remains uniform. It helps preserve food for longer.
 - Height-adjustable stainless steel legs. Height of the legs can be adjusted individually (130 mm - 200 mm) to enable convenient cleaning.
 - Low energy consumption LED lighting vertically located in the interior of compartment.
 - Stamped edge interiors, for easier cleaning operations to reduce potential dirt traps with a built-in drainage to get rid of waste liquid inside units.
 - Equipped with removable and height adjustable epoxy coated 3 x GN 2/1 grids with a maximum loading capacity of up to 40 kg.
 - Suitable for 1 x GN2/1 or 2 x GN1/1 food containers.
 - Mixed refrigeration and freezer cabinet.
 - Two independent modules with their respective refrigeration units and electronic controls.
- Refrigeration module:
- Forced draught refrigeration.
 - Working temperature: 0 °C, +8 °C.
- Freezer module:
- Forced draught evaporator.
 - Working temperature: -18 °C, -22 °C.

POSSIBLE OPTIONS :

- 60 Hz
- Stainless Backing
- Wheels Kit (Factory Assembly)
- Door frame resistance
- Locks
- Pedal

DIMENSIONS



X Width	1318 mm	X Gross width	1430 mm
Y Depth	842 mm	Y Gross depth	880 mm
Z Height	2040 mm	Z Gross height	2063 mm
Net Weight	302,0 kg	Gross Weight	320,0 kg
Net volume	2,264 m3	Gross volume	2,596 m3

ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	0,654 kW
Voltage	230V
Phases	1N
Electric frequency	50Hz
Amperage (A)	4,4 A

GAS TECHNICAL SPECIFICATIONS

Gas type 2	R-290
------------	-------

COLD TECHNICAL SPECIFICATIONS

Cooling gas load 2	150,000 g
Refrigeration power 2	0,535 kW
Temperature 2	-22 -18 °C
Temperature	0 +8 °C
Climate class	4
Refrigeration power	0,361 kW
GWP	3
Cooling gas load	98,000 g
Gross internal volume	1220 L
Noise level	62,00 dB
Condensation system	Vent.

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1+T-2A
--------------------------	----------

OTHERS

Number of doors	2
-----------------	---





Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CUD-22G/M FH 230V 1N 50Hz

19089470

17/07/2024

The photo may show the standard model and not the configured one

POSSIBLE ACCESSORIES :

- ACCESSORIES FOR REFRIGERATION
- GASTRONORM GRIDS

SUPPLIED ACCESSORIES:

- 19097787 GN 2/1 epoxi grid for GN 2/1 refrigerated upright. 6



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CUD-22G/M FH 230V 1N 50Hz

19089470

17/07/2024

