



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CUD-12G/N 230V 1N 50Hz

19089472

17/07/2024

The photo may show the standard model and not the configured one

DENOMINATION:

Concept gastronorm GN 2/1 dual temperature upright, single body with 2 doors.

DESCRIPTION :


- Interior constructed with AISI-304 stainless steel exterior in food grade stainless steel.
 - 50 mm insulation, with zipper and Removable guiding rails system.
 - Intuitive, digital display for electronic control with energy saving function to ensure an optimal control of storing products.
 - Stainless steel doors with ergonomic, full-length, robust, perfectly integrated handle. that ensures practical opening and avoids dust and dirt collection.
 - Removable pull-out/push-in magnetic door gasket to keep maximum hygiene and maintain the insulating properties.
 - Hinged doors with automatic return for a perfect closing that minimize temperature gain. Doors have a 120° dwell position and close automatically at less than 90°.
 - Pivotable panel with better access to control that facilitates service, thus enlarging the useful life of the equipment.
 - Automatic evaporation of defrost water.
 - Internally designed forced draft cooling system with low consumption electronic components to guarantee optimal equipment efficiency and performance.
 - Optimal air circulation system that guarantees a balanced and constant distribution throughout the equipment, so that the temperature remains uniform. It helps preserve food for longer.
 - Height-adjustable stainless steel legs. Height of the legs can be adjusted individually (130 mm - 200 mm) to enable convenient cleaning.
 - Low energy consumption LED lighting vertically located in the interior of compartment.
 - Stamped edge interiors, for easier cleaning operations to reduce potential dirt traps with a built-in drainage to get rid of waste liquid inside units.
 - Refrigeration compartment equipped with GN2/1 guides.
 - Freezer compartment equipped with 3 PVC 530X540 sanitary baskets.
 - Refrigeration cabinets with freezing compartment.
 - Equipment: 3 drawers in sanitary PVC Independent hermetic compressor with ventilated condenser.
 - Evaporator with copper pipe and aluminium cooling fins.
 - Environmentally-friendly refrigerant R-290. Forced draught refrigeration.
 - Automatic evaporation of frost water.
- Refrigeration module:
- Working temperature: from 0 °C to +8 °C.
- Freezing compartment:
- Working temperature: from -18 °C to -22 °C.
 - Refrigeration compartment with height adjustable epoxy coated GN 2/1 grids with a maximum loading capacity of up to 40 kg.
 - Freezer compartment equipped with 3 PVC 530X540 sanitary baskets.

POSSIBLE OPTIONS :

- 60 Hz
- Stainless Backing
- Wheels Kit (Factory Assembly)
- Door frame resistance

DIMENSIONS

X Width	693 mm	X Gross width	730 mm
Y Depth	826 mm	Y Gross depth	880 mm
Z Height	2008 mm	Z Gross height	2027 mm
Net Weight	167,0 kg	Gross Weight	175,0 kg
Net volume	1,149 m3	Gross volume	1,302 m3



ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	0,741 kW
Voltage	230V
Phases	1N
Electric frequency	50Hz
Amperage (A)	4,3 A

GAS TECHNICAL SPECIFICATIONS

Gas type 2	R-290
------------	-------

COLD TECHNICAL SPECIFICATIONS

Cooling gas load 2	102,000 g
Refrigeration power 2	0,364 kW
Temperature 2	-22 -18 °C
Temperature	0 +8 °C
Climate class	4
Refrigeration power	0,369 kW
GWP	3
Cooling gas load	98,000 g
Gross internal volume	596 L
Noise level	62,00 dB
Condensation system	Vent.

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1,5+T - 4 A
--------------------------	---------------

OTHERS

Number of doors	2
-----------------	---





Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CUD-12G/N 230V 1N 50Hz

19089472

17/07/2024

The photo may show the standard model and not the configured one

- Opposite Opening

POSSIBLE ACCESSORIES :

- ACCESSORIES FOR REFRIGERATION
- GASTRONORM GRIDS

SUPPLIED ACCESSORIES:

- 19010200 Tray support guides for fish compartments of dual GN 2/1 upright. 8
- 19010206 Tray support guides for refrigeration compartments of dual upright. 8
- 19097770 Plastic tray for freezing compartments of dual temperature upright. 3
- 19097787 GN 2/1 epoxi grid for GN 2/1 refrigerated upright. 1



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CUD-12G/N 230V 1N 50Hz

19089472

17/07/2024

